

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 58159036 A(43) Date of publication of application: 21.09.1983

(51) Int. Cl H04L 11/00

(21) Application number: 57042173(22) Date of filing: 17.03.1982

(54) COLLISION DETECTING DEVICE FOR COMMON SPECTRUM MULTIPLE ACCESS (CSMA)

(57) Abstract:

PURPOSE: To obtain a collision detecting device for CSMA, which is capable of detecting a collision in all states of a signal on a transmission line, by providing a circuit for detecting a fact that signal amplitude on the transmission line does not shown a state variation.

CONSTITUTION: In case of a regular collision, the collision can be detected by steeing the reference voltage V_2 of the second comparator 502 to about the center of -A and -2A, on the other hand, in case when two colliding send-out signals generate a signal pattern of entirely opposite polarity, the signal amplitude remains -A and no variation is generated in the amplitude as shown by a broken line, after t_1 . Accordingly, in this case, the condition that the signal amplitude is below V_1 and above V_2 is taken by the first and the second logical circuits 504, 505, and also the fact that

(71) Applicant: NEC CORP

(72) Inventor: HASEGAWA TOSHIO

there is no state variation of the signal is executed by a monostable multivibrator 503, by which the collision is detected.

COPYRIGHT: (C)1983, JPO&Japio



